




# 2 - 2026 US OPEN PATTERN 2



<b>DISTANCE:</b>	<b>47 FEET</b>	<b>VOLUME:</b>	<b>29.22 mL</b>
<b>RATIO:</b>	<b>1.63:1</b>	<b>FORWARD:</b>	<b>16.98 mL</b>
<b>DROP BRUSH:</b>	<b>34 FEET</b>	<b>REVERSE:</b>	<b>12.24 mL</b>
<b>TANKS:</b>	<b>CURVE &amp; GLIDE</b>	<b>PUMP:</b>	<b>MULTI</b>



### FORWARD LOADS DATA

#	START	STOP	LOADS	MICS	SPEED	BUFF	TANK	DISTANCE	T.OIL
1	2L	2R	2	60	14	500	A - CURVE	0 → 2	4,440
2	2L	2R	6	50	18	500	A - CURVE	2 → 17	11,100
3	13L	10R	2	40	18	500	A - CURVE	17 → 22	1,440
4	2L	2R	0	50	22	500	A - CURVE	22 → 34	0
5	2L	2R	0	50	22	350	A - CURVE	34 → 40	0
6	2L	2R	0	50	22	250	A - CURVE	40 → 44	0
7	2L	2R	0	50	22	150	A - CURVE	44 → 47	0

### REVERSE LOADS DATA

#	START	STOP	LOADS	MICS	SPEED	BUFF	TANK	DISTANCE	T.OIL
1	2L	2R	0	45	30	500	B - GLIDE	34 → 28	0
2	12L	12R	1	45	18	500	B - GLIDE	28 → 25	765
3	11L	11R	1	45	18	500	B - GLIDE	25 → 23	855
4	10L	10R	1	45	18	500	B - GLIDE	23 → 20	945
5	8L	8R	1	45	18	500	B - GLIDE	20 → 18	1,125
6	7L	7R	1	45	14	500	B - GLIDE	18 → 16	1,215
7	6L	6R	2	45	14	500	B - GLIDE	16 → 12	2,610
8	5L	5R	1	45	14	500	B - GLIDE	12 → 10	1,395
9	2L	2R	2	45	14	500	B - GLIDE	10 → 6	3,330
10	2L	2R	0	45	10	500	B - GLIDE	6 → 0	0

### THIS PATTERN IS DESIGNED FOR:

VARIABLE BUFFER SPEEDS | VARIABLE MICROLITER STREAMS | DUAL CONDITIONING TANKS | REVERSE DROP BRUSH  
 This pattern may require adjustments if using a lane machine that does not have these features

Created Mar 01, 2026 - Rendered for Atlas Pro.



**KEGEL PATTERN LIBRARY APP**



[PATTERNLIBRARY.KEGEL.NET](https://patternlibrary.kegel.net)



SCAN QR CODE FOR  
 MORE PATTERNS ON  
 KEGEL PATTERN  
 LIBRARY

