



STATIC WEIGHT REMOVAL CHART

		HOLE DEPTH IN INCHES										
		0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000
HOLE DIAMETER IN INCHES	19/32"	0.119	0.178	0.238	0.297	0.356	0.416	0.475	0.534	0.594	0.653	0.713
	5/8"	0.122	0.184	0.245	0.306	0.367	0.428	0.489	0.551	0.612	0.673	0.734
	21/32"	0.135	0.202	0.269	0.336	0.403	0.470	0.538	0.605	0.672	0.739	0.806
	11/16"	0.148	0.222	0.296	0.369	0.443	0.517	0.591	0.665	0.739	0.813	0.887
	23/32"	0.157	0.235	0.313	0.391	0.469	0.548	0.626	0.704	0.782	0.860	0.939
	3/4"	0.176	0.263	0.351	0.439	0.527	0.615	0.702	0.790	0.878	0.968	1.054
	25/32"	0.191	0.286	0.382	0.477	0.573	0.668	0.764	0.859	0.955	1.050	1.146
	13/16"	0.206	0.309	0.412	0.515	0.618	0.720	0.823	0.925	1.029	1.132	1.235
	27/32"	0.238	0.358	0.475	0.594	0.713	0.831	0.950	1.068	1.188	1.306	1.425
	7/8"	0.250	0.375	0.500	0.625	0.750	0.875	1.000	1.125	1.250	1.375	1.500
	29/32"	0.263	0.394	0.526	0.657	0.788	0.919	1.050	1.182	1.313	1.444	1.576
	15/16"	0.273	0.409	0.546	0.682	0.819	0.955	1.092	1.228	1.365	1.501	1.638
	31/32"	0.300	0.450	0.600	0.750	0.900	1.050	1.200	1.350	1.500	1.650	1.800
	1"	0.325	0.488	0.650	0.813	0.975	1.138	1.30	1.463	1.625	1.788	1.950
	1-1/32"	0.350	0.525	0.700	0.875	1.050	1.225	1.40	1.575	1.750	1.925	2.10
	1-1/16"	0.368	0.553	0.737	0.921	1.105	1.289	1.474	1.658	1.842	2.026	2.210
	1-3/32"	0.388	0.581	0.775	0.969	1.163	1.357	1.550	1.744	1.938	2.132	2.326
	1-1/8"	0.400	0.600	0.800	1.000	1.20	1.40	1.60	1.80	2.00	2.20	2.400
1-5/32"	0.425	0.638	0.851	1.063	1.275	1.488	1.700	1.913	2.125	2.338	2.55	
1-3/16"	0.450	0.675	0.900	1.125	1.350	1.575	1.800	2.025	2.250	2.475	2.700	
		WEIGHT REMOVED IN OUNCES										