

2016 U.S. Open FINAL 110216



Oil Pattern Distance	42	Reverse Brush Drop	38	Oil Per Board	Multi ul
Forward Oil Total	24.614 mL	Reverse Oil Total	7.35 mL	Volume Oil Total	31.964 mL
Tank Configuration	A-B	Tank A Conditioner	FIRE	Tank B Conditioner	ICE


5 2L 2R 1 40 18 3 37 25.7 28.2 2.5 1480 5 5L 5R 3 40 22 3 93 28.2 37.5 9.3 3720		START	STOP	LOADS	MICS	SPEED	BUFFER	CROSSED	START	END	FEET	T.OIL
3 4L 6R 2 55 10 3 62 17.8 20.6 2.8 3410 4 7L 8R 2 50 18 3 52 20.6 25.7 5.1 2600 5 2L 2R 1 40 18 3 37 25.7 28.2 2.5 1480 5 5L 5R 3 40 22 3 93 28.2 37.5 9.3 3720	1	2L	2R	4	48	18	3	148	0.0	7.6	7.6	7104
4 7L 8R 2 50 18 3 52 20.6 25.7 5.1 2600 5 2L 2R 1 40 18 3 37 25.7 28.2 2.5 1480 5 5L 5R 3 40 22 3 93 28.2 37.5 9.3 3720	2	2L	4R	4	45	18	3	140	7.6	17.8	10.2	6300
5 2L 2R 1 40 18 3 37 25.7 28.2 2.5 1480 5 5L 5R 3 40 22 3 93 28.2 37.5 9.3 3720	3	4L	6R	2	55	10	3	62	17.8	20.6	2.8	3410
5 5L 5R 3 40 22 3 93 28.2 37.5 9.3 3720	4	7L	8R	2	50	18	3	52	20.6	25.7	5.1	2600
	5	2L	2R	1	40	18	3	37	25.7	28.2	2.5	1480
7 2L 2R 0 50 10 3 0 37.5 42.0 4.5 0	6	5L	5R	3	40	22	3	93	28.2	37.5	9.3	3720
	7	2L	2R	0	50	10	3	0	37.5	42.0	4.5	0

	START	STOP	LOADS	MICS	SPEED	BUFFER	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	50	30	3	0	42.0	36.0	-6.0	0
2	15L	15R	3	50	30	3	33	36.0	23.3	-12.7	1650
3	15L	6R	2	50	30	3	40	23.3	14.8	-8.5	2000
4	2L	2R	2	50	30	3	74	14.8	6.3	-8.5	3700
5	2L	2R	0	50	10	3	0	6.3	0.0	-6.3	0
•	21	ZIX	·	30		,	U	0.5		0.0	0.0 -0.3

Cleaner Ratio Main Mix 5:1 Forward Cleaner Ratio Back End Mix 5:1 Reverse Cleaner Ratio Back End Distance 59 Combined Buffer RPM: $4 = 720 \mid 3 = 500 \mid 2 = 200 \mid 1 = 50$ Lanes will be double stripped each morning and lanes will be conditioned one (1) time per day in the morning.

8L-12L:18L-18R

3L-7L:18L-18R



escription	Outside Track:Middle	Middle Track:Middle	Inside Track:Middle	MIddle: Inside Track	Middle:Middle Track	Middle:Outside Track
ack Zone Ratio	1.58	1.3	1.1	1.06	1.16	1.73
1500 — — — — — — — — — — — — — — — — — —		!-#-#-#-#-				

13L-17L:18L-18R